

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Киргизия (996)312-96-26-47

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Казахстан (772)734-952-31

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Таджикистан (992)427-82-92-69

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

<https://twintex.nt-rt.ru/> || ttw@nt-rt.ru

Low-Cost Arbitrary Waveform/Function Generator



Product No : TFG3600E_Series

Product Description

The TFG3600E series are arbitrary waveform/function generators with maximum frequency of 5MHz, 10MHz, 15MHz and 20MHz, based on Direct Digital Synthesis (DDS) technology providing flexible performance and system features for basic scientific and industrial requirements.

The 8 bits resolution, 100MSa/s sampling rate, 1024 pts memory length, 32 built-in waveforms and 8 user-defined arbitrary waveforms create various waveforms for different needs. Free PC software for RS-232 interface control. The TFG3600E series have additional functions of multiple modulations FM, FSK, ASK and PSK, 200MHz external frequency counter, 40 sets memories and multiple protections. Stable output frequency, high accuracy and low distortion make TFG3600E series an ideal solution for an accurate and affordable signal source for industrial, scientific research and educational applications.

- ★ Max. output frequency 5MHz/10MHz/15MHz/20MHz
- ★ 2 output channels
- ★ 3.5-inch TFT LCD display
- ★ Direct Digital Synthesis technology (DDS)
- ★ Min. output amplitude 1mV (50Ω) with good stability
- ★ Sampling rate 100MSa/s, vertical resolution 8 bit, waveform length 1024 points
- ★ Arbitrary waveform function
- ★ 32 built-in waveforms and 8 user-defined arbitrary waveforms
- ★ 40 sets save & recall for panel settings
- ★ Modulations: FM, FSK, ASK, PSK
- ★ Frequency sweep, amplitude sweep, burst and TTL output functions
- ★ Over voltage, over current, short circuit and reverse voltage protections
- ★ High speed rotary dial and keypad input
- ★ Standard RS-232 interface for PC remote control
- ★ Standard 200MHz external frequency counter
- ★ Optional power amplifier

Model		TFG-3605E	TFG-3610E	TFG-3615E	TFG-3620E
Output frequency		1μHz~5MHz	1μHz~10MHz	1μHz~15MHz	1μHz~20MHz
Waveform					
Output waveform		32 built-in waveforms, including Sine, Square, Triangle, Ramp, Pulse, etc. 8 user-defined arbitrary waveforms			
Waveform length		1024 points			
Vertical resolution		8 bits			
Sampling rate		100MSa/s			
Sine	Harmonic distortion	≥40dBc (<1MHz); ≥35dBc (1~20MHz)			
	Total distortion	≤1% (20Hz~200kHz)			
Square	Rise/fall time	≤35ns			
	Overshoot	≤10%			
	Duty cycle	1%~99%			
Frequency					
Range	Sine	1μHz~5MHz	1μHz~10MHz	1μHz~15MHz	1μHz~20MHz
	Square	1μHz~5MHz			
	Other	1μHz~1MHz			
Resolution		1μHz			
Accuracy		±5x10 ⁻⁵			
Stability		±5x10 ⁻⁶ /3hours			
Output characteristics					
Amplitude	Range	2mVpp~20Vpp (open circuit, ≤10MHz)			
		2mVpp~15Vpp (open circuit, 10MHz~15MHz)			
		2mVpp~8Vpp (open circuit, 15MHz~20MHz)			
	Resolution	20mVpp (amplitude>2Vpp); 2mVpp (amplitude<2Vpp)			
	Accuracy	±(1%+2mVrms) (open circuit, 1kHz, sine)			
	Stability	±0.5% /3hours			
	Flatness	±5% (<10MHz); ±10% (>10MHz)			
	Output impedance	50Ω			
Offset	Range	±10V (open circuit, attenuation 0 dB)			
	Resolution	20mVdc			
	Accuracy	±(1%+20mVdc)			
Sweep					
Parameter		Frequency, Amplitude			
Range		Free to set start and stop point			

Time	100ms~900s
Direction	Up, Down, Up-Down
Mode	Linearity, Logarithmic
Control	Auto sweep or manual sweep
Frequency Modulation (FM)	
Carrier signal	CHA signal
Modulating signal	CHB or external signal
Deviation	0%~20%
Shift Keying	
FSK	Free to set the hop frequency and the carrier frequency
ASK	Free to set the hop amplitude and the carrier amplitude
PSK	Hop phase: 0~360°, resolution: 1°
Alternative rate	10ms~60s
Burst	
Carrier signal	CHA signal
Trigger signal	TTL_A signal
Burst counts	1~65000 cycles
Trigger source	Internal TTL, External, Single
CHB output characteristics	
Output waveform	32 built-in waveforms, including Sine, Square, Triangle, Ramp, Pulse, etc. 8 user-defined arbitrary waveforms
Waveform length	1024 points
Vertical resolution	8 bits
Sampling rate	12.5MSa/s
Frequency range	Sine: 1μHz~1MHz; Other: 1μHz~100kHz
Frequency resolution	1μHz
Frequency accuracy	±1x10 ⁻⁵
Amplitude range	50mVpp~20Vpp (open circuit)
Amplitude resolution	20mVpp
Output impedance	50Ω
CHB signal is used as burst signal	
Carrier signal	CHB signal
Trigger signal	TTL_B signal
Burst counts	1~65000 cycles
Trigger source	Internal TTL, External, Single

TTL output	
Waveform	Square, rise/fall time ≤20ns
Frequency	10mHz~1MHz
Amplitude	TTL, CMOS compatible, low<0.3V, high>4V
Frequency counter	
Frequency range	1Hz~200MHz
Input amplitude	100mVpp~20Vpp
Power amplifier (optional)	
Max. output power	7W (8Ω), 1W (50Ω)
Max. output voltage	22Vpp
Frequency bandwidth	1Hz~200kHz
General	
Operation characteristics	Key operation for all functions, Menu display, Rotary dial adjustment
Display	3.5-inch TFT LCD
Language	English, Chinese (simplified), Chinese (traditional)
Interface	RS-232 interface
Operating environment	0~40°C, <80%RH
Power source	AC110V/220V±10% selectable, 50/60Hz, Max. 45VA
Accessories	Power cord x1, Operation manual x1, Software CD x1, RS-232 cable x1, BNC-BNC cable x1, Test lead x1
Dimension(WxHxD)	260x110x385mm
Weight	3.5kg

Архангельск (8182)63-90-72
Астана (7172)727-132
Астрахань (8512)99-46-04
Барнаул (3852)73-04-60
Белгород (4722)40-23-64
Брянск (4832)59-03-52
Владивосток (423)249-28-31
Волгоград (844)278-03-48
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-89
Иваново (4932)77-34-06

Ижевск (3412)26-03-58
Иркутск (395)279-98-46
Казань (843)206-01-48
Калининград (4012)72-03-81
Калуга (4842)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Липецк (4742)52-20-81
Киргизия (996)312-96-26-47

Магнитогорск (3519)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-64-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)227-86-73
Омск (3812)21-46-40
Орел (4862)44-53-42
Оренбург (3532)37-68-04
Пенза (8412)22-31-16
Казахстан (772)734-952-31

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-64
Самара (846)206-03-16
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)22-31-93
Симферополь (3652)67-13-56
Смоленск (4812)29-41-54
Сочи (862)225-72-31
Ставрополь (8652)20-65-13
Таджикистан (992)427-82-92-69

Сургут (3462)77-98-35
Тверь (4822)63-31-35
Томск (3822)98-41-53
Тула (4872)74-02-29
Тюмень (3452)66-21-18
Ульяновск (8422)24-23-59
Уфа (347)229-48-12
Хабаровск (4212)92-98-04
Челябинск (351)202-03-61
Череповец (8202)49-02-64
Ярославль (4852)69-52-93

<https://twintex.nt-rt.ru/> || ttw@nt-rt.ru