

Архангельск (8182)63-90-72
 Астана (7172)727-132
 Астрахань (8512)99-46-04
 Барнаул (3852)73-04-60
 Белгород (4722)40-23-64
 Брянск (4832)59-03-52
 Владивосток (423)249-28-31
 Волгоград (844)278-03-48
 Вологда (8172)26-41-59
 Воронеж (473)204-51-73
 Екатеринбург (343)384-55-89
 Иваново (4932)77-34-06

Ижевск (3412)26-03-58
 Иркутск (395)279-98-46
 Казань (843)206-01-48
 Калининград (4012)72-03-81
 Калуга (4842)92-23-67
 Кемерово (3842)65-04-62
 Киров (8332)68-02-04
 Краснодар (861)203-40-90
 Красноярск (391)204-63-61
 Курск (4712)77-13-04
 Липецк (4742)52-20-81
 Киргизия (996)312-96-26-47

Магнитогорск (3519)55-03-13
 Москва (495)268-04-70
 Мурманск (8152)59-64-93
 Набережные Челны (8552)20-53-41
 Нижний Новгород (831)429-08-12
 Новокузнецк (3843)20-46-81
 Новосибирск (383)227-86-73
 Омск (3812)21-46-40
 Орел (4862)44-53-42
 Оренбург (3532)37-68-04
 Пенза (8412)22-31-16
 Казахстан (772)734-952-31

Пермь (342)205-81-47
 Ростов-на-Дону (863)308-18-15
 Рязань (4912)46-61-64
 Самара (846)206-03-16
 Санкт-Петербург (812)309-46-40
 Саратов (845)249-38-78
 Севастополь (8692)22-31-93
 Симферополь (3652)67-13-56
 Смоленск (4812)29-41-54
 Сочи (862)225-72-31
 Ставрополь (8652)20-65-13
 Таджикистан (992)427-82-92-69

Сургут (3462)77-98-35
 Тверь (4822)63-31-35
 Томск (3822)98-41-53
 Тула (4872)74-02-29
 Тюмень (3452)66-21-18
 Ульяновск (8422)24-23-59
 Уфа (347)229-48-12
 Хабаровск (4212)92-98-04
 Челябинск (351)202-03-61
 Череповец (8202)49-02-64
 Ярославль (4852)69-52-93

<https://twintex.nt-rt.ru/> || ttw@nt-rt.ru

Tachometer

Product No : TT – 735B



Specifications

| | |
|--------------------|--|
| Range | Contact rotation speed: 0.5~19,999 r/min Contact line speed (Metric): 0.05~1999.9 m/min Contact line speed (Imperial): 0.2~6560 ft/min |
| Accuracy | ±(0.05%+1) |
| Resolution | Contact rotation speed: 0.1 RPM (0.5~999.9 RPM); 1 r/min (>1000 RPM) Contact line speed (Metric): 0.01 m/min (0.05~99.99 m/min); 0.1 m/min (>100 m/min) Contact line speed (Imperial): 0.1 ft/min (0.1~999.9 ft/min); 1 ft/min(>1000 ft/min) |
| Sampling time | 0.5s (>120 r/min) |
| Range selection | Auto range |
| Power consumption | Max.45mA |
| Memory | Auto memory Max./Min., Last value and Auto memory for 96 groups data |
| Time base | 6MHz Quarts crystal |
| Time base accuracy | 10x10 ⁻⁶ (0°C~50°C) |
| Battery | 4x1.5V AA |
| Meter Size | 160x72x37mm |
| Max. Display | 19999 |
| LCD size | 5 digits LCD display |
| Accessories | Battery, Carrying case, Reflecting tape marks, Damp proof accessory, Bolt bag, Contact speed measurement fitting, Contact rotational speed measurement fitting, User manual |